

Hose Valves

Hose valves of 1 1/2 in. (38 mm) may be used on connections from sprinkler systems; 2 1/2 in. (64 mm) valves are used on hose standpipes and fire pump headers. For pressures above 175 psi (1205 kPa), an appropriate pressure reducing device shall be used.

Hose Valves, Angle

Fig. A97 & A99 / A99H

<i>Model</i>	<i>Description</i>	<i>Nominal Size, in</i>	<i>Rated Working Pressure, psi (kPa)</i>
A97	Angle Hose Valve, FNPT x FNPT	1-1/2, 2-1/2	300 (2070)
A97	Angle Hose Valve, FNPT x MNST	1-1/2, 2-1/2	300 (2070)
A97	Angle Hose Valve, Groove x MNST	2-1/2	300 (2070)
A97	Angle Hose Valve Groove x FNPT	2-1/2	300 (2070)
A99	Pressure Restricting Angle Hose Valve, FNPT x Male NH	1-1/2, 2-1/2 (38, 64 mm)	175 (1205)
A99H	Pressure Restricting Angle Hose Valve, FNPT x FNPT	1-1/2, 2-1/2 (38, 64 mm)	175 (1205)

Company Name:	Ban Chang Hardware Co Ltd
Company Address:	No. 17 Lane 620, Sec 3 Lu Ho Rd, Lu Kang Chang Hua, Taiwan (R.O.C)
Company Website:	http://www.banchang.com.tw
New/Updated Product Listing:	No
Listing Country:	Taiwan
Certification Type:	FM Approved